

C60L/C60LP

Enterprise Entry Level Cost Effective
IP Phone



C60L/C60LP



Key Features

- HD Voice
- 2 SIP Accounts
- 2 Line keys
- 5-way Conference
- 132x64 pixel Graphical LCD
- 1* 10/100Mbps Ethernet
- Support EHS wireless heads
(Plantronics, Jabra, Sennheiser)
- Stand with 2 adjustable angles
- Full Compatible with 3CX, Asterisk,
Yeastar, Xorcom, VoIP.ms, Broadsoft,
FreeSWITCH Platform etc.

Benefits

A Cost-effective Business IP Phone

The C60L/C60LP is an entry-level IP Phone, which can be applied to various IP Voice Phone systems. The C60L/C60LP not only integrates a 132x64 pixel graphic LCD and an elegant and intuitive user interface, but also supports high-definition voice calls and other calling functions, which can fully meet the needs of users in various industries.

Good Compatibility

Based on RFC3261, the C60L/C60LP has been tested to ensure good compatibility with leading IP telephony system and equipment. The C60L/C60LP not only supports Dinstar UC/IPPBX products, also supports many third-party IPPBXs such as 3CX, Asterisk, Yeastar, Xorcom, VoIP.ms and so on.

High Quality Audio

The full duplex speaker and microphone system and the Digital Signal Processor (DSP) ensure that the C60L/C60LP delivers high audio quality. Whether you use the hands-free speakerphone or the handset, you will always have good experience and crystal-clear call quality.

Model	Screen	Network	PoE Support	Power Adapter
C60L	132x64	1*10/100M	x	√
C60LP	132x64	1*10/100M	√	Optional

Call Features

- 2 SIP Accounts
- Call Waiting
- Call Forward
- Blind/attended transfer
- Call hold, Call mute, DND mode
- Speed Dialing, Hotline
- Redial, Call Return
- Auto-redial, Auto-answer
- Dial Plan
- 5-way conference
- Peer Dialing

Phone Features

- Adjustable Voice Volume
- Selectable Ring Tones
- XML Browser
- Action URL/URI
- Keyboard lock
- Phonebook: 1,000 Groups
- Blacklist: 100 Groups
- Call Log: 100 Logs
- Support 5 Remote Phonebook URLs
- LDAP
- Support Multiple Languages
- Support EHS wireless headset(Plantronics, Jabra, Sennheiser)

IP-PBX Features

- SMS, Voicemail, MWI
- Music On-hold, Intercom, Multicast
- Call Pickup, Call Pickup in Group
- Anonymous Call
- Anonymous Call Rejection

Management

- Auto provisioning:
FTP/TFTP/HTTP/HTTPS/PnP
- Configuration via HTTP/HTTPS web
- SNMP, TR069
- Network capture
- NTP/Daylight saving time
- Firmware upgrade via web
- Syslog
- Configuration backup/restore
- Equipment Management System (NMS)

Audio

- HD Voice
- Wideband Codec: G.722, OPUS-WB
- Narrowband Codec: PCMA, PCMU, G.729, G723, G726, AMR, OPUS, iLBC
- Echo Cancellation/Dynamic Jitter
- Voice Activity Detection (VAD)
- Comfort Noise Generation (CNG)
- Full-duplex Speaker

Protocols & Standards

- SIP v1 (RFC2543) , SIP v2 (RFC3261)
- SIP over TLS, SRTP
- TCP/IP/UDP
- RTP/RTCP, RFC2198, RFC1889
- HTTP/HTTPS/FTP/TFTP
- ARP/RARP/ICMP/NTP/DHCP
- DNS SRV/ A Query/NATPR Query
- STUN, Session Timer (RFC4028)
- DTMF: In-Band, RFC2833, SIP INFO
- LLDP
- OpenVPN, 802.1X

Physical Features

- 132x64 pixel graphic LCD
- Dual-angle foot stand: 40° and 45°
- Dimensions(approx.):
180x192x36mm(WxLxD) without foot stand
- Weight(approx.): device 370g, foot stand 60g
- Input voltage: 5Vdc
- Power supply: 5Vdc power adapter or PoE
- Power consumption: 1.4W
- Handset: 4P4C, RJ9
- Headset: 4P4C, RJ9
- Environmental conditions:
Operation temperature: 0°C ~ 45°C
Storage Temperature: -10°C ~ 60°C
Humidity: 10% to 90% (non-condensing)
- 1xRJ45 10/100M Ethernet Ports
- Wall Mountable